

NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETRES.
- 2. FOR PITS NOT IN TRAFFIC LANES, THE STANDARD SHAFT SIZE IS MIN. 900Ø.
- 3. PIT LIDS IN TRAFFICABLE AREA TO BE CLASS 'D' GATIC OR SIMILAR APPROVED.
- 4. PIT LIDS IN NON TRAFFICABLE AREAS TO BE CLASS 'C'
- 5. OTHER PITS MAY BE UTILISED FOLLOWING APPROVAL BY THE MILDURA RURAL CITY COUNCIL REPRESENTATIVE.
- 6. REFER TO AS3996 FOR LOAD CLASSIFICATIONS.
- 7. FOR PITS DEEPER THAN 1.0m PROVIDE GALVANISED PLASTIC ENCAPSULATED STEP IRONS, INSTALLED AS PER AS1657. PITS DEEPER THAN 2400 SHALL BE FITTED WITH A LADDER.
- 8. ALL STEP IRONS / LADDERS TO BE SPACED EQUALLY AS PER AS1657. ACCEPTABLE RUNG SPACING IS BETWEEN 250 MIN TO 300 MAX TO SUIT PIT DEPTH.



Mildura Rural City Council

108 - 116 Madden Avenue Mildura, Vic. 3500 Ph: (03) 5018 8100

TYPICAL PRECAST STORMWATER JUNCTION PIT

REVISION: 1 SHEET: A3 SCALE: NTS DATE: 22/10/22 APPROVED: J. JEYAKANTHAN DRAWING No: MSD-100