

#### NOTE:

- 1. COMPACTED BACKFILL TO BE SITE WON MATERIAL OR SIMILAR.
- 2. HAUNCH ZONE TO BE APPROVED SAND MATERIAL.
- 3. BEDDING ZONE TO BE COMPACTED APPROVED SAND MATERIAL DEPTH TO BE 100mm MIN. FOR DIA. < 1500mm AND 150mm MIN. FOR DIA. > 1500mm.
- 4. CLEARANCE 'X' O.D./3. MINIMUM 150mm AND MAXIMUM 300mm UNLESS OTHERWISE SPECIFIED.
- 5. COMPACTION TO BE 95% S.M.D.D. BY CHARACTERISTIC VALUE OF DENSITY RATIO (IN 150mm LAYERS)
- 6. TESTING IS NOT REQUIRED AT THIS STAGE.
- 7. TRENCHES THROUGH EXISTING LANDSCAPED AREAS TO HAVE THE TOP 100mm FILLED WITH LOAM AND SEEDED TO MATCH EXISTING WHERE REQUIRED.

## PIPE BACKFILL DETAIL - LANDSCAPED AREAS N.T.S.

### NOTE:

- ALL DIMENSIONS ARE IN MILLIMETRES UNLESS NOTED OTHERWISE.
- RECYCLED BEDDING AND BACKFILL MATERIAL CAN BE SUBSTITUTED ON APPROVAL OF MRCC REPRESENTATIVE.



## Mildura Rural City Council

108 - 116 Madden Avenue Mildura, Vic. 3500 Ph: (03) 5018 8100

# PIPE BACKFILL DETAILS LANDSCAPED AREAS

REVISION: 1 SHEET: A3 SCALE: NTS DATE: 22/10/22 APPROVED: J. JEYAKANTHAN DRAWING No: MSD-131